



MiniRAE Lite

Portable Handheld VOC Monitor



The MiniRAE Lite is the most reliable handheld volatile organic compound (VOC) monitor on the market. Its photoionization detector's (PID) range of 0 to 5,000 ppm makes it an ideal instrument for applications ranging from environmental to construction.

KEY FEATURES

- Proven PID technology—The patented sensor provides the following unique features:
 - 3-second response time
 - Range up to 5,000 ppm
 - Humidity compensation
- Designed for service—Easy access to lamp and sensor in seconds without tools
- Big graphic display for easy overview of concentration
- Field-interchangeable battery pack, replaceable in seconds without tools
- Integrated flashlight for better visibility in low light
- Multi-language support with 12 languages encoded
- Rugged housing withstands use in harsh environments
 - IP-65 design
 - Strong, protective removable rubber boot

ADDITIONAL ADVANTAGES

- Duty-cycling™ lamp and sensor auto-cleaning technology
- Tough, flexible inlet Flexi-Probe™
- Large keys are operable with 3 layers of gloves
- Strong, built-in sample pump draws up to 100' (30m) horizontally or vertically
- Loud, 95 dB audible alarm
- Bright red flashing visible alarm
- Interchangeable drop-in Lithium-ion and alkaline battery packs
- 3-year 10.6 eV lamp warranty

- Accurate VOC monitoring
- Fastest response time (3 sec)
- Humidity compensation
- Easy to maintain and operate
- Three-year lamp warranty



MiniRAE Lite



Portable Handheld VOC Monitor

SPECIFICATIONS

Sensor Specifications

Gas Monitor	Range (ppm)	Resolution (ppm)	Response Time (T90)
VOCs	0 to 999.9	0.1	< 3 sec
VOCs	1000 to 5,000	1	< 3 sec

Monitor Specifications

Size	10" L x 3.0" W x 2.5" H (25.5 x 7.6 x 6.4 cm)
Weight	26 oz (738 g)
Sensors	Photoionization sensor with standard 10.6eV lamp
Battery	<ul style="list-style-type: none">Alkaline battery adapterExternal field-replaceable lithium-ion battery pack, if specified
Operating Hours	12 hours of operation on alkaline battery adapter (12 hours with lithium-ion battery pack)
Display Graphic	4 lines, 28 x 43 mm, with LED back light
Keypad	1 operation and 2 programming keys, 1 flashlight on/off
Direct Readout	Instantaneous reading of: <ul style="list-style-type: none">VOCs as ppm by volumeHigh and low valuesDate and time
Alarms	95 dB buzzer (at 30 cm) and flashing red LED to indicate exceeded preset limits <ul style="list-style-type: none">High: 3 beeps and flashes per secondLow: 2 beeps and flashes per secondAlarm latching with manual override or automatic resetAdditional diagnostic alarm and display message for low battery and pump stall
EMI/RFI	<ul style="list-style-type: none">Highly resistant to EMI/RFI.Compliant with EMC directive 89/336/EEC
IP Rating	IP-65
Calibration	Two-point calibration for zero and span
Sampling Pump	<ul style="list-style-type: none">Internal, integrated flow rate at 400 cc/minSample from 100' (30m) horizontally and vertically
Low Flow Alarm	Auto shut-off pump at low-flow condition
Hazard Area Approval	None
Operating Temperature	-4° to 113° F (-20° to 50° C)
Humidity	0 to 95% relative humidity (non-condensing)
Attachments	Durable green rubber boot
Warranty	3 years for 10.6 eV lamp, 1 year for pump, battery and instrument

Specifications are subject to change

MINIRAE LITE ORDERING OPTIONS

Monitor only includes:

- MiniRAE Lite Monitor, Model PGM-7300
- RAE Systems 10.6 eV UV lamp
- Flex-I-Probe
- External filter
- Green rubber boot
- Alkaline battery adapter
- Lamp cleaning kit
- Tool kit
- Lithium-ion (Li-ion) battery, if specified with universal AC/DC charger and international plug kit
- Travel charger, if specified
- Universal wall adapter, if specified
- Operation & Maintenance manual
- Soft leather carrying case

Monitor with accessories kit adds:

- Hard transport case with pre-cut foam padding
- 5 Porous metal filters and O-rings
- Organic vapor zeroing kit
- Gas outlet port adapter and tubing

Optional calibration kit adds:

- 100 ppm isobutylene calibration gas, 34L
- Calibration regulator and flow controller

ORDERING INFORMATION

- Monitor only with alkaline battery adapter (PN 059-A100-000)
- Monitor with rechargeable Li-ion battery, accessory and calibration kit (PN 059-A110-100)